

## PRODUCT DATA

**LUSIN® CLEAN 61-205**

Cleaner on organic solvent base

**Benefits:**

- Degreases and cleans thoroughly
- Specially designed for tool cleaning in plastics processing
- Suitable for ultrasonic cleaning

**Typical Performance Characteristics**

Colour	colourless
Flash Point per DIN 53213	> 26 °C
Density g/cm <sup>3</sup>	≈ 0,75

**Product description**

For the removal of resin, oil, grease or wax residues from plastic and metal parts.

Particularly suitable for the degreasing of tools and moulds for plastic processing.

**Application/Dilutions**

The contaminated parts should be sprayed thoroughly with LUSIN® CLEAN 61-205 and, if necessary, left to react for several minutes and wiped with a cloth.

As this product dissolves resins very effectively, plastic parts should be checked for resistance before they are cleaned. LUSIN® CLEAN 61-205 can also be used as a thinner.

The cleaned parts can be protected from corrosion by applying a film of LUSIN® PROTECT G11 or LUSIN® PROTECT G31.

**Storage / Handling**

Store in a dry place at room temperature in original sealed packing.

For further information on storage, handling, hazards, etc. please refer to safety data sheet.

**Shelf life:** approx. 1 year from production date

**Packaging**

Canister 20 L

Drum 200 L

Code N° : 273292

1

**Further Information**

Request information on our complete range of materials for this industry.

<sup>1</sup> † While the technical information and suggestions for use contained herein are believed to be accurate and reliable, nothing stated in this bulletin is to be taken as a warranty either expressed or implied.