

PRODUCT DATA

Lusin® Protect O 45

Grease based anticorrosive with foodstuff approval

Benefits:

- foodstuff approved
- stable, transparent protective film
- repels water

Typical Performance Characteristics

Temperature range	Up to 80 °C
Corrosion protection per DIN 50017 on steel type RST-37-2	No corrosion after 40 hours
Salt water spray test per DIN 50021 on steel type 101-A	No corrosion after 50 hours

Product description

LUSIN® PROTECT O 45 is a grease based transparent anticorrosive for the temporary protection of all metal surfaces. It is approved for use in the production of all foodstuff appliances.

LUSIN® PROTECT O 45 is silicone-free and does not attack plastics. When sprayed on to metal surfaces it forms an even film which penetrates even very fine cracks and repels water.

LUSIN® PROTECT O 45 spraycans contain environmentally friendly propellant.

Application

LUSIN PROTECT O 45 is used mainly to protect moulds and dies for plastic processing. When these tools are put back into operation it is not necessary to remove the film of PROTECT O 45. If the parts produced are to be painted or printed on, a test is recommended.

Instructions for use

To protect metal surfaces a fine even film is sufficient. When spraying sufficient ventilation is important.

Shelf life :

- 2 years

Storage / Handling

For further information on storage, handling, hazards, etc. please refer to safety data sheet.

Packaging

Spraycan 400 ml (12 cans in one carton)

Code No. 040070

1

Further Information

Request information on our complete range of materials for this industry.

Chem-Trend (Deutschland) GmbH
Ganghoferstr. 47, D - 82216 Maisach / Gernlinden
Telephone: +49 8142 417-0 Facsimile: +49 8142 158 84 Email: maisach@chemtrend.de
Copyright © 2004 Chem-Trend L.P., All Rights Reserved